

United States Patent [19] Okabe

[11] Patent Number: 4,807,276

[45] **Date of Patent:** Feb. 21, 1989

- [54] RE-TRANSMISSION METHOD AND APPARATUS IN COMMUNICATION SYSTEM USING PUBLIC COMMUNICATION LINES**

[75] Inventor: Shinichi Okabe, Hitachi, Japan

[73] Assignee: Hitachi, Ltd., Tokyo, Japan

[21] Appl. No.: 147,325

[22] Filed: Jan. 22, 1988

[30] Foreign Application Priority Data

Jan. 24, 1987 [JP] Japan 62-14472

[51] Int. Cl.⁴ H04M 11/00; H04N 1/32

[52] U.S. Cl. 379/93; 379/100;
178/1; 178/2 R

[58] Field of Search 379/93, 100; 358/280,
358/305; 178/1, 2 R, 3, 4, 4.1 B

[56] **References Cited**

U.S. PATENT DOCUMENTS

4,471,489 9/1984 Konetski et al. 379/93

4,595,951 6/1986 Fulliman 358/147

4,710,951	12/1987	Hezono	379/100
-----------	---------	--------------	---------

FOREIGN PATENT DOCUMENTS

62257561 7/1985 Japan .

Primary Examiner—Stafford D. Schreyer

Attorney, Agent, or Firm—Antonelli, Terry & Wands

[57] **ABSTRACT**

In a communication system having an automatic transmission/reception function to perform data communi-

cations through telephone lines associated with teletex systems, facsimile systems and the like, re-transmission operations are performed when an addressee called for communications is busy (calling) or when communications is interrupted after an addressee has responded. In the re-transmission operation, a response from an addressee is detected and decided as to whether the response is automatically originated from a communication unit or originated by a person. When the latter response is detected, a wrong telephoning is decided and restrictions are placed on the re-transmission operation to thereby minimize trouble given to the addressee. On the condition that a wrong telephoning and a communication failure transmission operation are decided, the addressor station sequentially reduces the calling time or response waiting time in the communication system for each of re-transmission operations following the communication failure transmission operation, and on the condition that a response is received but no negotiation is settled within a predetermined period of time whereby a wrong telephoning and a communication failure transmission operation are decided, the addressor station inhibits communication operations following the communication failure transmission operation when time runs within a midnight discount time zone and permits the communication operations, inclusive of the initial transmission operation, to be performed twice when time runs outside the midnight discount time zone.

13 Claims, 7 Drawing Sheets

